

# PERSONAL MONITOR



The Personal Monitor features a dome and string mechanism that is attached to the patient's garment. When an unassisted exit takes place, the dome is pulled from its magnetic socket and an alarm sounds. The alarm is silenced when the dome is placed back into the socket. The Personal Monitor can be applied quickly, and moved easily from one location to another.

## EASE OF USE

- ▶ "Alarm", "Low Battery", and "In Use" indicator LEDs show status at a glance

## FLEXIBILITY

- ▶ Nurse call jack allows direct notification to nurse call
- ▶ Bed, chair, and wall mount options are available

## SAFETY

- ▶ Magnetic dome allows activation when pulled from any direction
- ▶ Volume control located within the battery compartment deters patients from changing the volume level

## DURABILITY

- ▶ Durable thick plastic casing and impact-resistant rubberized edging reduces replacement/repair costs
- ▶ Two Year Warranty

## SPECIFICATIONS

- ▶ Size: 5.3" H x 3.5" W x 1.7" D
- ▶ Power Source: 4 AA batteries (included)
- ▶ Manufactured to ISO9001, conforms to ANSI/UL standard 1069, certified to CAN/CSA C2.2 #205



## ACCESSORIES

Model	Model Number
Pull String/Magnetic Dome Replacement with Linen Clip	CSM-PS-L40
Replacement Velcro Strap	CSM-VS
8' jumper cable to connect the monitor to the nurse call system	JU96-295